



# LinkPoint® 3000




**The next generation** in point-of-sale terminal technology, the LinkPoint 3000 delivers a high-performance, reliable and easy-to-use payment solution for merchants. The LinkPoint 3000's state-of-the-art technology meets complex processing demands, with quick transaction times, enhanced functionality and heightened security—all at an affordable price.

An intuitive ATM-style interface makes the LinkPoint 3000 easy to learn and easy to use.

Its screen-addressable keys and dedicated function keys offer more selections with fewer steps. A fast modem and internal processor ensure the speediest transaction times. Compatible with many industry-standard peripherals, the LinkPoint 3000 provides maximum versatility at the merchant site.



# LinkPoint 3000



## Superior Reliability

- Reduces long-term merchant support expenses
- 12-month warranty provides peace of mind

## Unbeatable Performance

- Fast, secure processing keeps pace with merchants' transaction needs
- Supports all payment processing methods—credit, debit, checks, loyalty programs, etc.

## Maximum Merchant Efficiency

- Intuitive ATM-style interface makes learning a snap
- Clearly labeled, dedicated function keys simplify everyday operations
- Screen-addressable keys provide more selections with fewer steps
- Two-line display is easy to read in all lighting conditions

## Versatility at the Merchant Site

- Supports multiple languages and multiple merchant identifications
- Calculator function provides added-value module
- Compatible with many industry-standard peripherals (PIN pads, check readers, etc.)

## Compact Design

- Small footprint provides the greatest convenience
- Base or wall mounting saves valuable counterspace

## Advanced Fraud Prevention

- Password protection prevents unauthorized downloads
- Manager password controls ensure transaction security

## Specifications

- **Memory:** 256 K battery-backed RAM (standard); up to 1 Mb RAM (optional).
- **Screen:** Two-line, 20-character backlit LCD.
- **Keypad:** 30 alphanumeric keys.
- **Magnetic card reader:** track 1 and track 2, bidirectional.
- **Peripheral Ports:** 8-pin DIN RS-232 port for printers 6-pin DIN port for PIN pads, smart card readers or bar-code wands 8-pin DIN RS-232 general-purpose port for check readers, etc.
- **Communications:** Modem: asynchronous 300/1,200 BPS standard Bell 103/212A, V.21/V.22 internal (synchronous optional). Telco: standard modular jacks (2).
- **Physical:** 1.98 in. (50.4 mm) H X 5.60 in. (143.1 mm) W X 6.50 in. (165.4 mm) L, 1.25 lb. (0.54 kg). Net shipping weight (including power adapter): 2.74 lb. (1.24 kg).
- **Power:** 120 VAC, 50/60 Hz. Power consumption: 450 mA, idle; 500 mA, off hook. Power adapter: 9 VAC, 1.2 amps.
- **Environmental:** Temperature: 32° to 104°F (0° to 40°C). Operating humidity: 10% to 90%, noncondensing.
- **Warranty:** Standard 12-month warranty.