## Magtek Mini MICR - Omni/VX

This check is designed to configure a Magtek Mini MICR check reader to interface with a Verifone Omni/VX terminal.

Insert this check, beginning on the left side of the reader, with the check face towards the inside of the reader. After successful configuration, the green LED will blink 8 times.

If at any point the LED turns red, repeat this process until successful configuration is achieved.

\*THIS IS NOT A TEST CHECK\*

Please cut as close to the line as possible to ensure readability

Item #: C-2 Check: 1 of 1

For Technical Assistance Contact: 1-877-438-3249

© Paya Services 2018

.''.'O 154" 360000:1000 2:::000:'

## Magtek Mini MICR - Omni/VX

This check is designed to configure a Magtek Mini MICR check reader to interface with a Verifone Omni/VX terminal.

Insert this check, beginning on the left side of the reader, with the check face towards the inside of the reader. After successful configuration, the green LED will blink 8 times.

If at any point the LED turns red, repeat this process until successful configuration is achieved.

\*THIS IS NOT A TEST CHECK\*

Please cut as close to the line as possible to ensure readability

Item #: **C-2**Check: 1 of 1

For Technical Assistance Contact: 1-877-438-3249

© Paya Services 2018

.''.'O 154" 360000:1000 2:::000.'

## Magtek Mini MICR - Omni/VX

This check is designed to configure a Magtek Mini MICR check reader to interface with a Verifone Omni/VX terminal.

Insert this check, beginning on the left side of the reader, with the check face towards the inside of the reader. After successful configuration, the green LED will blink 8 times.

If at any point the LED turns red, repeat this process until successful configuration is achieved.

\*THIS IS NOT A TEST CHECK\*

Please cut as close to the line as possible to ensure readability

Item #: C-2 Check: 1 of 1

For Technical Assistance Contact: 1-877-438-3249

© Paya Services 2018

.''.''O 1 5 4 ||\* 3 6 0 0 0 0 1 0 0 0 2 ||\* 0 0 0 0 |

## Magtek Mini MICR - Omni/VX

This check is designed to configure a Magtek Mini MICR check reader to interface with a Verifone Omni/VX terminal.

Insert this check, beginning on the left side of the reader, with the check face towards the inside of the reader. After successful configuration, the green LED will blink 8 times.

If at any point the LED turns red, repeat this process until successful configuration is achieved.

\*THIS IS NOT A TEST CHECK\*

Please cut as close to the line as possible to ensure readability

Item #: C-2
Check: 1 of 1

For Technical Assistance Contact: 1-877-438-3249

© Paya Services 2018

."."O 154" 3600001:000 2...000."