

Magtek Imager - Omni/VX

This check is designed to configure a Magtek Imager to interface with a Verifone Omni/VX terminal.

Insert this check, beginning on the left side of the imager, with the check face towards the inside of the reader. After successful configuration, the green LED will blink 4 times.

If at any point the LED turns red, repeat this process until successful configuration is achieved.

THIS IS NOT A TEST CHECK

Please cut as close to the line as possible to ensure readability

Item #: **C-7**

Check: 1 of 1

For Technical Assistance

Contact: 1-877-438-3249

© Paya Services 2018

0 2 28 0000 2 1 240 2 260 300 14 240 500 26000 7000 8000

Magtek Imager - Omni/VX

This check is designed to configure a Magtek Imager to interface with a Verifone Omni/VX terminal.

Insert this check, beginning on the left side of the imager, with the check face towards the inside of the reader. After successful configuration, the green LED will blink 4 times.

If at any point the LED turns red, repeat this process until successful configuration is achieved.

THIS IS NOT A TEST CHECK

Please cut as close to the line as possible to ensure readability

Item #: **C-7**

Check: 1 of 1

For Technical Assistance

Contact: 1-877-438-3249

© Paya Services 2018

0 2 28 0000 2 1 240 2 260 300 14 240 500 26000 70008000.

Magtek Imager - Omni/VX

This check is designed to configure a Magtek Imager to interface with a Verifone Omni/VX terminal.

Insert this check, beginning on the left side of the imager, with the check face towards the inside of the reader. After successful configuration, the green LED will blink 4 times.

If at any point the LED turns red, repeat this process until successful configuration is achieved.

THIS IS NOT A TEST CHECK

Please cut as close to the line as possible to ensure readability

Item #: **C-7**

Check: 1 of 1

For Technical Assistance

Contact: 1-877-438-3249

© Paya Services 2018

0 2 28 0000 2 1 240 2 260 300 14 240 500 26000 7000 8000

Magtek Imager - Omni/VX

This check is designed to configure a Magtek Imager to interface with a Verifone Omni/VX terminal.

Insert this check, beginning on the left side of the imager, with the check face towards the inside of the reader. After successful configuration, the green LED will blink 4 times.

If at any point the LED turns red, repeat this process until successful configuration is achieved.

THIS IS NOT A TEST CHECK

Please cut as close to the line as possible to ensure readability

Item #: C-7

Check: 1 of 1

For Technical Assistance

Contact: 1-877-438-3249

© Paya Services 2018

0 2 28 0000 2 1 240 2 260 300 14 240 500 26000 7000 8000