Magtek MICR-Image - Hypercom/Equinox

This check is designed to configure a Magtek Imager to interface with a Hypercom/Equinox T4100/T4200 series terminal.

Insert this check, beginning on the left side of the imager, with the check face towards the inside of the reader. After successful configuration, the green LED will blink 4 times.

If at any point the LED turns red, repeat this process until successful configuration is achieved.

THIS IS NOT A TEST CHECK

Please cut as close to the line as possible to ensure readability

Item #: **C-8**Check: 1 of 1

For Technical Assistance Contact: 1-877-438-3249

© Paya Services 2018

Magtek MICR-Image - Hypercom/Equinox

This check is designed to configure a Magtek Imager to interface with a Hypercom/Equinox T4100/T4200 series terminal.

Insert this check, beginning on the left side of the imager, with the check face towards the inside of the reader. After successful configuration, the green LED will blink 4 times.

If at any point the LED turns red, repeat this process until successful configuration is achieved.

THIS IS NOT A TEST CHECK

Please cut as close to the line as possible to ensure readability

Item #: C-8
Check: 1 of 1

For Technical Assistance Contact: 1-877-438-3249

© Paya Services 2018

Magtek MICR-Image - Hypercom/Equinox

This check is designed to configure a Magtek Imager to interface with a Hypercom/Equinox T4100/T4200 series terminal.

Insert this check, beginning on the left side of the imager, with the check face towards the inside of the reader. After successful configuration, the green LED will blink 4 times.

If at any point the LED turns red, repeat this process until successful configuration is achieved.

THIS IS NOT A TEST CHECK

Please cut as close to the line as possible to ensure readability

Item #: **C-8**Check: 1 of 1

For Technical Assistance Contact: 1-877-438-3249

© Paya Services 2018

··'·'O 2 3 1··''OOOO 2 1640 2 300 304 14 140 5 20 16000 7000B000 ·'

Magtek MICR-Image - Hypercom/Equinox

This check is designed to configure a Magtek Imager to interface with a Hypercom/Equinox T4100/T4200 series terminal.

Insert this check, beginning on the left side of the imager, with the check face towards the inside of the reader. After successful configuration, the green LED will blink 4 times.

If at any point the LED turns red, repeat this process until successful configuration is achieved.

THIS IS NOT A TEST CHECK

Please cut as close to the line as possible to ensure readability

Item #: C-8
Check: 1 of 1

For Technical Assistance Contact: 1-877-438-3249

© Paya Services 2018

.,','O 2 3 1,"'OOOO 2 1,6 4,0 2 300 30 4 1 4 1 40 5 20 1,6000 7000B000,'