

Magtek Mini MICR serial connection - TPI Software

Item #: **C-21**

Check: 1 of 1

This check is designed to configure a Magtek Mini MICR check reader to interface with the TPI gateway software.

Insert this check, beginning on the left side of the reader, with the check face towards the inside of the reader. After successful configuration, the green LED will blink 8 times.

If at any point the LED turns red, repeat this process until successful configuration is achieved.

THIS IS NOT A TEST CHECK

For Technical Assistance

Contact: 1-877-438-3249

© Paya Services 2018



Magtek Mini MICR serial connection - TPI Software

Item #: **C-21**

Check: 1 of 1

This check is designed to configure a Magtek Mini MICR check reader to interface with the TPI gateway software.

Insert this check, beginning on the left side of the reader, with the check face towards the inside of the reader. After successful configuration, the green LED will blink 8 times.

If at any point the LED turns red, repeat this process until successful configuration is achieved.

THIS IS NOT A TEST CHECK

For Technical Assistance

Contact: 1-877-438-3249

© Paya Services 2018



Magtek Mini MICR serial connection - TPI Software

Item #: **C-21**

Check: 1 of 1

This check is designed to configure a Magtek Mini MICR check reader to interface with the TPI gateway software.

Insert this check, beginning on the left side of the reader, with the check face towards the inside of the reader. After successful configuration, the green LED will blink 8 times.

If at any point the LED turns red, repeat this process until successful configuration is achieved.

THIS IS NOT A TEST CHECK

For Technical Assistance

Contact: 1-877-438-3249

© Paya Services 2018



Magtek Mini MICR serial connection - TPI Software

Item #: **C-21**

Check: 1 of 1

This check is designed to configure a Magtek Mini MICR check reader to interface with the TPI gateway software.

Insert this check, beginning on the left side of the reader, with the check face towards the inside of the reader. After successful configuration, the green LED will blink 8 times.

If at any point the LED turns red, repeat this process until successful configuration is achieved.

THIS IS NOT A TEST CHECK

For Technical Assistance

Contact: 1-877-438-3249

© Paya Services 2018

